



GU10 Semi Recessed Downlight



CODE: DL2028
FINISH: TEXTURED WHITE(RAL9003)
TEXTURED BLACK(RAL9005)



GENERAL

LOCATION:	Interior
CLASS:	CE (Class III)
IP RATING:	IP20
INSTALLATION ORIENTATION:	Ceiling Recessed
MAIN MATERIAL:	Aluminum
CUT OUT HOLE (mm):	Ø: 64

LIGHT SOURCE

LIGHT SOURCE:	LED Module/GU10&MR16 lamp
WATTAGE:	Max.13W/Max.7W(LED only)
LAMP INCLUDED:	No
MAXIMUM LAMP LENGTH (mm):	78/59
LUMINOUS FLUX (lm):	780lm@2700K Ra.90/Lamp Dependent
COLOUR TEMP (K):	2700~4000K/Lamp Dependent
CRI (Ra):	Ra.90/Lamp Dependent
MACADAM ELLIPSE:	3 Steps/Lamp Dependent
LIFETIME (hrs):	50,000hrsB20L90/Lamp Dependent
BEAM ANGLE (°):	20(S)~40(M)~60(W)/Lamp Dependent

ELECTRICAL(LED Module only)

DIMMABLE:	Yes
DIMMING METHOD:	Phase-cut/0-10V/Dali
SUPPLY FREQUENCY (Hz):	50/60Hz
DRIVER VOLTAGE (V):	220-240V
DRIVER LIFETIME (hrs):	50,000hrs

ADDITIONAL INFORMATION

ACCESSORIES	Honeycomb louver Clear/fross/prismatic diffuser
DO NOT COVER MARK:	Not suitable for mounting on flammable materials



For more information of this product or its family products, installation, maintenance, and guarantee policy, please view our website: www.vjclighting.com The information presented in this specification sheet might be modified by the manufacturer without notification.