

Phantom Anti Glare LED

Phantom Frosted Mini Matt Black Round Recessed Uplight 60° 700mA
2700K Warm White 3W



FR2119RDH 60BK2K

2700K Warm White 3W
Quicklink: Q68A7

General

Colour	Black
Construction	Steel / Glass
Dimmable	Yes
IP Rating	IP68

Dimensions

Cable Length	2m
Cut Out	33mm (Diameter)
Depth	42mm
Diameter	40mm
Minimum Floor	42mm
Depth	

Electrical

Amperage	700mA
Maximum Wattage	3W

Light Characteristics

Beam Angle	60°
Colour Temperature	2700K Warm White
Lumens	140 lm
Lumens Per Watt	47 lm/W

The **Phantom Round** is a small recessed uplight with a honeycomb baffle to reduce glare, that can be used in floors and walls. It is rated IP68, allowing it to be fitted into wet areas such as shower cubicles or outside in decking. It can be placed in zones 0, 1 and 2 of bathrooms, offering full flexibility in its placement.

The fitting comes complete with spring clips to mount into hollow walls and floors. It also comes with a plastic mounting tube for use with brick and other solid surfaces. If used outside, it is strongly advised that *Heat Shrink* is used to protect the wiring from water.

Please note; this product requires a 700mA driver and must be wired in series.

LED Driver Options

- Switching - Use this driver for on/off control. Cannot be used for dimming.
- Dimming - Use this driver for dimming control. Some dimmers may require a resistive dummy load to meet the minimum load requirements.
- Dimming - 1-10V - Use this driver with a 1-10V dimmer modules or control systems. This type of dimming does not have a minimum load.

For a step-by-step guide to install outdoor ground uplights in the earth, lawn, decking or patio, [click here](#).

Phantom Anti Glare LED

Phantom Frosted Mini Matt Black Round Recessed Uplight 60° 700mA
2700K Warm White 3W

