

## product code

IPR-PICRSS

## name

Piccadilly Round, SSS3I6, IP67, CREE XPE, 700mA, 20° Beam, 3W, 3000K, driver excl.

## description

Piccadilly Round SS

## technical data sheet



## item

<b>finish</b>	Grade 316 Satin Stainless Steel	<b>bathroom zones</b>	1 & 2
<b>main material</b>	Aluminium	<b>tilt angle</b>	N/A
<b>overall dimensions</b>	dia.40 x h.53mm	<b>adjustable</b>	N/A
<b>application</b>	Outdoor Recessed	<b>warranty</b>	5 years
<b>cut out</b>	36mm	<b>avg hours of operation</b>	30000
<b>recess depth</b>	92	<b>weight rating</b>	N/A
<b>fire rated</b>	No	<b>nett weight</b>	0.2
<b>ip rating</b>	IP67		

## light

<b>light source</b>	CREE XPE
<b>lumen output</b>	175
<b>colour temperature (cct)</b>	3000K (Warm White)
<b>cri</b>	>80
<b>beam angle</b>	20
<b>efficacy (lm/w)</b>	58
<b>lamp detail</b>	N/A
<b>lamp included?</b>	N/A

## electrical

<b>maximum wattage</b>	3
<b>input power</b>	700mA
<b>driver included?</b>	No
<b>power factor</b>	N/A
<b>switch</b>	N/A
<b>dimmable</b>	Yes
<b>dimming method</b>	When used with a dimmable driver
<b>class</b>	3 (Low Voltage)
<b>cable length</b>	1500

## additional information

Must be wired in series, Driver supplied separately

Installation tube included

# project

collection

## technical drawings

Includes  
installation tube

