

## product code

PE-ARA100-W

## name

Ara ø100cm Pendant, 3000k-4000k switchable, TRIAC Dimmable, Sand White

## description

Ara 100, White



## item

|                           |                                   |                               |         |
|---------------------------|-----------------------------------|-------------------------------|---------|
| <b>finish</b>             | Sand White                        | <b>bathroom zones</b>         | N/A     |
| <b>main material</b>      | Frosted Acrylic                   | <b>tilt angle</b>             | N/A     |
| <b>overall dimensions</b> | dia.1000 x h. 70, max drop 2000mm | <b>adjustable</b>             | Height  |
| <b>application</b>        | Ceiling                           | <b>warranty</b>               | 5 years |
| <b>cut out</b>            | N/A                               | <b>avg hours of operation</b> | 30000   |
| <b>recess depth</b>       | N/A                               | <b>weight rating</b>          | N/A     |
| <b>fire rated</b>         | N/A                               | <b>nett weight</b>            | 4.35    |
| <b>ip rating</b>          | IP20                              |                               |         |

## light

|                                 |                       |
|---------------------------------|-----------------------|
| <b>light source</b>             | SMD LED               |
| <b>lumen output</b>             | 5600                  |
| <b>colour temperature (cct)</b> | 3000/4000k switchable |
| <b>cri</b>                      | >80                   |
| <b>beam angle</b>               | 120                   |
| <b>efficacy (lm/w)</b>          | 93                    |
| <b>lamp detail</b>              | N/A                   |
| <b>lamp included?</b>           | N/A                   |

## electrical

|                         |                  |
|-------------------------|------------------|
| <b>maximum wattage</b>  | 60               |
| <b>input power</b>      | 220-240V 50/60Hz |
| <b>driver included?</b> | Yes              |
| <b>power factor</b>     | 0.95             |
| <b>switch</b>           | N/A              |
| <b>dimmable</b>         | Yes              |
| <b>dimming method</b>   | Mains            |
| <b>class</b>            | 1 (Earthed)      |
| <b>cable length</b>     | 2000             |

## additional information

Ceiling can D240xH45mm  
 5400 lumens at 3000K, 5600 lumens at 4000K  
 switch in ceiling can to change CCT 3000k or 4000k  
 Minimum drop 50cm, Max drop. 3m

# project

collection

## technical drawings

