

## product code

CE-VER40-W


## name

Verve 40, Trio CCT, TRIAC, IP44, White

## description

Verve 40, White

## technical data sheet



## item

<b>finish</b>	Sand white	<b>bathroom zones</b>	N/A
<b>main material</b>	Aluminium / PC Diffuser	<b>tilt angle</b>	N/A
<b>overall dimensions</b>	Dia. 422mm x 58mm	<b>adjustable</b>	N/A
<b>application</b>	Ceiling / Suspended	<b>warranty</b>	5 years
<b>cut out</b>	N/A	<b>avg hours of operation</b>	50,000
<b>recess depth</b>	N/A	<b>weight rating</b>	N/A
<b>fire rated</b>	N/A	<b>nett weight</b>	N/A
<b>ip rating</b>	IP44		

## light

<b>light source</b>	Integrated LED
<b>lumen output</b>	2100 lumens at 3000K, 2300 lumens at 4000K, 2100 lumens at 5700K
<b>colour temperature (cct)</b>	3000K / 4000K / 5700K
<b>cri</b>	>80
<b>beam angle</b>	N/A
<b>efficacy (lm/w)</b>	N/A
<b>lamp detail</b>	SMD LED
<b>lamp included?</b>	N/A

## electrical

<b>maximum wattage</b>	23
<b>input power</b>	N/A
<b>driver included?</b>	N/A
<b>power factor</b>	0.9
<b>switch</b>	N/A
<b>dimmable</b>	Yes
<b>dimming method</b>	Mains
<b>class</b>	2
<b>cable length</b>	N/A

## additional information

Rear or side cable entry  
 CCT switch on back of fitting  
 Add PA-VER to suspend from 200mm up to 2m, n.b. IP20  
 IES/LDT files supplied for 4000K

# project

collection

## technical drawings

